

SAFETY DATA SHEET

VAPOR LOCK[™] 0/0

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

PRODUCT NAME	VAPOR LOCK [™] 0/0		
PRODUCT USE	A ready to use water-based penet weatherproofing.	rating sealer for concrete for sealing, ha	rdening, dustproofing, waterproofing and
MANUFACTURER'S NAME		Specialty Products Group	
	6254 Skyway Rd, PO Box 915	Tel 1-877-957-4626	3909 Witmer Rd Suite 1014
	Smithville ON LOR 2A0	Fax 1-905-527-0606	Niagara Falls NY 14305
SUPPLIER'S NAME		SPG Australia P: 08 8426 0352 E: info@spggogreen.com.au	PO Box 33, Adelaide Airport SA 5950
EMERGENCY NUMBER	Emergency Services Poisons Information Line (24hrs)	000 13 11 26	

2. HAZARDS IDENTIFICATION



GHS CLASSIFICATION: Flammability 5, Reactivity 5, Health 4

ROUTE OF ENTRY	Eye contact, Ingestion, Inhalation, Skin contact.
CARCINOGENIC STATUS	Not considered carcinogenic by NTP, IARC, and OSHA.
TARGET ORGANS	Eye, Skin, and lungs
HEALTH EFFECTS – EYE	Moderate irritation expected
HEALTH EFFECTS – SKIN	Moderate irritation expected.
HEALTH EFFECTS – INGESTION	May cause irritation to the mouth, esophagus and stomach and damage to kidney (chronic ingestion)
HEALTH EFFECTS – INHALATION	Spray mist is irritating to the respiratory system.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients are proprietary

4. FIRST AID MEASURES

FIRST AID – INHALATION	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention.
FIRST AID – SKIN	Immediately flood the skin with large quantities of water. Remove contaminated clothing and shoes. Obtain medical attention.
FIRST AID – EYE	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention.
FIRST AID – INGESTION	If swallowed, Obtain medical attention immediately. If victim is fully conscious, give a cupful of milk. If conscious induce vomiting. Never give anything by mouth to an unconscious person.
INFORMATION FOR DOCTOR	

Most important symptoms and effects, both acute and delayed.

No further relevant information

Indications of any immediate medical attention and special treatment needed. No further relevant information available.

5. FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY	Non-flammable. Will not support combustion.
EXTINGUISHING MEDIA	Is compatible with all extinguishing media.
SPECIAL HAZARDS OF PRODUCT	Dries to form glass film which can easily cut the skin. Spilled material is very slippery. Can etch glass if not promptly removed.
PROTECTIVE EQUIPMENT FOR FIRE FIGHTING	Wear full protective clothing when this material is present in the area of the fire.
EXPLOSION DATA – SENSITIVITY TO IMPACT	N/A
EXPLOSION DATA – SENSITIVITY TO STATIC	N/A
DISCHARGE	

VAPOR LOCK[™] 0/0

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES	Small spills – Mop up and neutralize liquid, dispose in accordance with federal, provincial and local regulations or
	permits.
	Large spills – Isolate hazard area. Do not touch or walk through spilled material. Isolate, dike and store discharged
	material, if possible. Use sand or earth to contain material. If containment is impossible, neutralize contaminated
	area and flush with large quantities of water.
PERSONAL PRECAUTIONS	Wear chemical goggles, body-covering protective clothing, chemical resistant gloves and rubber boots. Use a
T ERGENAET REGACTIONS	NIOSH-approved dust and mist respirator where spray mist occurs.
ENVIRONMENTAL PRECAUTIONS	Prevent the material from entering drains or watercourses. Notify authorities if spill has entered watercourse or
	sewer.
REFERENCES TO OTHER SECTIONS	
See Section 7 for information on safe handling	

See Section 8 for information on personal protection equipment See Section 13 for disposal information

7. HANDLING AND STORAGE

HANDLING	Avoid contact with eyes, skin and clothing. Avoid breathing mist. Keep container closed. Promptly clean up spills.	
STORAGE	Keep container closed. Store in clean steel or plastic containers. Separate from acids, reactive metals and ammonium salts. Storage	
	temperature 0-95 deg C. Do not store in aluminum, fiberglass, copper, brass, zinc or galvanized containers.	
INFORMATION	INFORMATION ABOUT PROTECTION AGAINST EXPLOSION AND FIRE	
Keep ignition so	Keep ignition sources away – Do not smoke	
Protect against	Protect against electrostatic charges	
SPECIFIC END USE(S)		
No further relevant information available		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within
	direct access.
RESPIRATORY PROTECTION	Use a NIOSH-approved dust and mist respirator where spray mist occurs. Observe Provincial regulations for
	respiratory use.
HAND PROTECTION	Full-length gloves should be worn during all handling operations. Neoprene gloves.
EYE PROTECTION	Chemical goggles should be worn during all handling operations to protect against splashing.
BODY PROTECTION	Discard contaminated protective equipment. If there is danger of splashing, wear overall or apron.
PROTECTION DURING APPLICATION	During application, adequate ventilation must be provided. Mix in a well-ventilated area. If ventilation is poor,
	wear respiratory protection. Dries to form glass film which can easily cut the skin. Spilled material is very
	slippery. Can etch glass if not promptly removed.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid	
ODOR & APPEARANCE	Odorless, clear	
ODOR THRESHOLD (ppm)	NA	
SPECIFIC GRAVITY	1.07 – 1.10	
VAPOR DENSITY (AIR = 1)	ND	
VAPOR PRESSURE at 20°C	ND	
EVAPORATION RATE	ND	
BOILING POINT (°C)	ND	
FREEZING POINT (°C)	ND	
pH	10-12	
COEFFICIENT OF WATER/OIL DISTRIBUTION	ND	
SOLUBILITY IN WATER	Miscible	
VOC (g/L)	0	
FLASH POINT (PMCC) (°C/°F)	Non-flammable.	
UPPER FLAMMABLE LIMIT %VOL	NA	
LOWER FLAMMABLE LIMIT %VOL	NA	
AUTOIGNITION TEMP (°C/°F)	NA	

VAPOR LOCK[™] 0/0

10. STABILITY AND REACTIVITY

STABILITY	Stable under normal conditions
CONDITIONS TO AVOID	Do Not Freeze
MATERIALS TO AVOID	Gels and can generate heat when mixed with acid. May react with ammonium salts resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead and zinc. May react with strong oxidizing agents.
HAZARDOUS POLYMERIZATION	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS	Hydrogen gas.

11. TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE	Irritation to the eyes and skin is expected. Irritation and burning sensation of mouth, throat, nausea, vomiting and abdominal pain. On inhalation of liquid will cause irritation to mucous membranes, coughing and wheezing.
EFFECTS OF CHRONIC EXPOSURE	May cause dermatitis and irritation on repeated contact.
EXPOSURE LIMITS	NA
IRRITANCY	Moderate irritation expected
SENSITIZATION	ND
CARCINOGENICITY	Not listed as a carcinogen by IARC, NTP or OSHA.
REPRODUCTIVE TOXICITY	ND
TERATOGENICITY	ND
MUTAGENICITY	ND
TOXICOLOGICALLY SYNERGISTIC PRODUCTS	ND

12. ECOLOGICAL INFORMATION

MOBILITY	Sinks and mixes with water. Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica.
PERSISTENCE/DEGRADABILITY	This product is not persistent in aquatic systems, but its high pH when undiluted or un-neutralized is harmful to aquatic life. Full ecological impact has not been determined.
BIO-ACCUMULATION	Neither silica nor sodium will appreciably bioconcentrate up the food chain.
ECOTOXICITY	The following data is reported for sodium silicate on a 100% basis: A 96-hour median tolerance for: Fish (Gambusia affnis) of 2320 ppm; Water fleas (Daphnia magna) of 247 ppm; Snail eggs (Lymnea) of 632 ppm; (Amphipoda) of 160 ppm.
RESULTS of PBT and vPvB Assessm PBT: N/A vPvB: N/A	

13. DISPOSAL CONSIDERATIONS

PRODUCT DISPOSAL	Absorb product on an inert material (sand or earth) and transfer absorbed product into a waste container. Dispose of in
	accordance with all applicable local and national regulations.
CONTAINER DISPOSAL	Labels should not be removed from containers until they have been cleaned. Empty containers may contain hazardous
	residues. Dispose of containers with care.
UNCLEANED PACKAGINGS	
Recommendation: Disposal must be made according to official regulations	

14. TRANSPORTATION INFORMATION

AUSTRALIA	TDG CLASSIFICATION
HAZARD LABEL NOT REQUIRED	NOT REGULATED, Keep from freezing
EXPORT	
DOT CFR 172.101 DATA	NOT REGULATED
UN PROPER SHIPPING NAME	NA
UN CLASS	NA
UN NUMBER	NA
UN PACKAGING GROUP	NA
FLASH POINT	NA
HAZARDOUS MATERIAL	NA
HAZARD LABEL	NA
MARINE POLLUTANT	NO
SPECIFIC PRECAUTIONS FOR USER	M/A

15. REGULATORY INFORMATION

WHMIS CLASSIFICATION: CLASS D, DIV.2, SUBDIVISION B-Material causing other toxic effects. CEPA STATUS (DSL): All of the ingredients of this product are listed on the Domestic Substances List. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by CPR.

16. OTHER INFORMATION

HEALTH4FLAMMABILITY5REACTIVITY5PERSONAL PROTECTION	HMIS Hazard 5-MINIMAL 4-SLIGHT 3-MODERAT 2-SERIOUS 1-SEVERE	0-MINIMAL 1-SLIGHT	
KEY	NA:	No applicable information found or available	
	CAS#:	Chemical Abstracts Service Number	
	ACGIH:	American Conference of Governmental Industrial Hygienists	
	OSHA:	Occupational Safety and Health Administration	
	TLV:	Threshold Limit Value	
	PEL:	Permissible Exposure Limit	
	STEL:	Short Term Exposure Limit	
	NTP:	National Toxicology Program	
	IARC:	International Agency for Research on Cancer	
	R:	Risk	
	S:	Safety	
	LD50:	Lethal Dose 50%	
	LC50:	Lethal Concentration 50%	

PREPARED BY:	SPG Australia
ISSUE DATE:	26/09/2022
REASON FOR ISSUE:	Revised

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.