

# SPECIALTY SAFETY DATA SHEET

## VAPOR LOCK™ SCS 120

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

PRODUCT NAME	VAPOR LOCK SCS 120™		
PRODUCT USE	Water-based concrete admixture th	at stops the route of moisture migration	
MANUFACTURER'S NAME	Specialty Products Group		
	6254 Skyway Rd, PO Box 915	Tel 1-877-957-4626	3909 Witmer Rd Suite 1014
	Smithville ON L0R 2A0	Fax 1-905-527-0606	Niagara Falls NY 14305
SUPPLIER'S NAME		SPG Australia P: 08 8426 0352 E: info@spggogreen.com.au	PO Box 33, Adelaide Airport SA 5950
EMERGENCY NUMBER	Emergency Services Poisons Information Line (24hrs)	000 13 11 26	

#### 2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION: Flammability 5, Reactivity 5, Health 4		
ROUTE OF ENTRY	Eye contact, Ingestion, Inhalation, Skin contact.	
CARCINOGENIC STATUS	Not considered carcinogenic by NTP, IARC, and OSHA.	
TARGET ORGANS	Eye, Skin, and lungs	
HEALTH EFFECTS – EYE	Moderate irritation expected	
HEALTH EFFECTS – SKIN	Moderate irritation expected.	
HEALTH EFFECTS – INGESTION	May cause irritation to the mouth, esophagus and stomach and damage to kidney, central nervous system and	
	blood.	
HEALTH EFFECTS – INHALATION	Spray mist is irritating to the respiratory system.	

### 3.COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients are non-hazardous and proprietary	

### 4. FIRST AID MEASURES

	No inhalation hazard expected.	
FIRST AID – SKIN	Rinse skin with water. Remove contaminated clothing and shoes.	
FIRST AID – EYE	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention.	
FIRST AID – INGESTION	If swallowed, rinse mouth with water if discomfort or diarrhea persist call for medical assistance.	
INFORMATION FOR DOCTOR		
Most important symptoms and effects, both acute and delayed.		
No further relevant information		
Indications of any immediate medical attention and special treatment needed.		
No further relevant information available.		

#### 5. FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY	Non-flammable. Will not support combustion.
EXTINGUISHING MEDIA	Is compatible with all extinguishing media.
SPECIAL HAZARDS OF PRODUCT	Dries to powdery material.
PROTECTIVE EQUIPMENT FOR FIRE FIGHTING	N/A
EXPLOSION DATA – SENSITIVITY TO IMPACT	N/A
EXPLOSION DATA – SENSITIVITY TO STATIC DISCHARGE	N/A

#### 6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES	Small spills – Mop up and allow to enter drain or dispose of in accordance with federal, provincial and local	
	regulations or permits. Large spills: dispose of in accordance with federal, provincial and local regulations or	
	permits. No special requirements.	
PERSONAL PRECAUTIONS	Minimize exposure	
ENVIRONMENTAL PRECAUTIONS	Unless for intended use, prevent entry into water system	
REFERENCES TO OTHER SECTIONS		
See Section 7 for information on safe handling		
See Section 8 for information on personal protection equipment		
See Section 13 for disposal information		

REV: 26092022 1 of 4

### VAPOR LOCK™ SCS 120

### 7. HANDLING AND STORAGE

HANDLING	Avoid contact with eyes, skin and clothing. Keep container closed.		
STORAGE	Keep container closed. Store in plastic containers.		
INFORMATION AE	INFORMATION ABOUT PROTECTION AGAINST EXPLOSION AND FIRE		
Not a fire or explosive hazard			
SPECIFIC END USE(S)			
No further relevant information available			

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.
RESPIRATORY PROTECTION	None
HAND PROTECTION	Wash hands after use
EYE PROTECTION	Avoid splashing or spray into eyes
BODY PROTECTION	Avoid body contact – wash or rinse any sprayed area
PROTECTION DURING APPLICATION	No special protection required

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
ODOUR & APPEARANCE	Light green liquid
ODOR THRESHOLD (ppm)	NA NA
SPECIFIC GRAVITY	1.01 -1.03
VAPOR DENSITY (AIR = 1)	ND
VAPOR PRESSURE at 20°C	ND
EVAPORATION RATE	ND
BOILING POINT (°C/°F)	100°C (212°F)
FREEZING POINT (°C/°F)	ND
pH	10-12
COEFFICIENT OF WATER/OIL DISTRIBUTION	6.5 - 7.5
SOLUBILITY IN WATER	Miscible
VOC (g/L)	0
FLASH POINT (PMCC) (°C/°F)	Non-flammable.
UPPER FLAMMABLE LIMIT %VOL	NA NA
LOWER FLAMMABLE LIMIT %VOL	NA NA
AUTOIGNITION TEMP (°C/°F)	NA NA

### 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal conditions
CONDITIONS TO AVOID	Do Not Freeze
MATERIALS TO AVOID	None
HAZARDOUS POLYMERIZATION	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS	None

## 11. TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE	Irritation to the eyes and skin is expected. Mild irritation to mouth, throat, nausea, vomiting, and abdominal pain. On inhalation of liquid will cause irritation to mucous membranes.
EFFECTS OF CHRONIC EXPOSURE	NA NA
EXPOSURE LIMITS	NA NA
IRRITANCY	Moderate irritation expected
SENSITIZATION	ND
CARCINOGENICITY	Not listed as a carcinogen by IARC, NTP or OSHA.
REPRODUCTIVE TOXICITY	ND
TERATOGENICITY	ND ND
MUTAGENICITY	ND ND
TOXICOLOGICALLY SYNERGISTIC PRODUCTS	ND

REV: 26092022 2 of 4

### VAPOR LOCK™ SCS 120

### 12. ECOLOGICAL INFORMATION

MOBILITY	Completely miscible with water	
PERSISTENCE/DEGRADABILITY	This product is not persistent in aquatic systems	
BIO-ACCUMULATION	Not know to bio-accumulate	
ECOTOXICITY	None known	

### 13. DISPOSAL CONSIDERATIONS

PRODUCT DISPOSAL	Dispose of in accordance with all applicable local and national regulation. No special method required	
CONTAINER DISPOSAL	Labels should not be removed from containers until they have been cleaned.	
UNCLEANED PACKAGINGS		
Recommendation: No special method required		

### 14. TRANSPORTATION INFORMATION

CANADA	TDG CLASSIFICATION
HAZARD LABEL NOT REQUIRED	NOT REGULATED, Keep from freezing
EXPORT	
DOT CFR 172.101 DATA	NOT REGULATED
UN PROPER SHIPPING NAME	NA
UN CLASS	NA
UN NUMBER	NA
UN PACKAGING GROUP	NA
FLASH POINT	NA
HAZARDOUS MATERIAL	NA
HAZARD LABEL	NA
MARINE POLLUTANT	NA
SPECIFIC PRECAUTIONS FOR USER	NA

### 15. REGULATORY INFORMATION

WHMIS CLASSIFICATION: Not regulated

CEPA STATUS (DSL): All of the ingredients of this product are listed on the Domestic Substances List.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by CPR.

#### 16. OTHER INFORMATION



KEY

HMIS hazard ID:

5-MINIMAL; 4-SLIGHT; 3-MODERATE; 2-SERIOUS;

1-SEVERE

O CAMPAGE IT O REACTIVITY PROTECTIVE RESIDENT

NFPA hazard ID:

0-MINIMAL; 1-SLIGHT; 2-MODERATE; 3-SERIOUS;

4-SEVERE

NA:	No applicable information found or available
CAS#:	Chemical Abstracts Service Number
ACGIF	: American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety and Health Administration
TLV:	Threshold Limit Value
PEL:	Permissible Exposure Limit
STEL:	Short Term Exposure Limit
NTP:	National Toxicology Program
IARC:	International Agency for Research on Cancer
R:	Risk
S:	Safety
LD50:	Lethal Dose 50%
LC50:	Lethal Concentration 50%

REV: 26092022 3 of 4

## VAPOR LOCK™ SCS 120

PREPARED BY:	SPG Australia
ISSUE DATE:	26/09/2022
REASON FOR ISSUE:	Revised

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.

REV: 26092022 4 of 4